

## STRAIGHT VALVES

### H-41

Tubeless spud, used with all Large Bore swivel valves.  
Fits 13/16" rim hole.



H-41

### H-42

Straight valve, equipped with core and hex cap.



H-42



H-45

### H-45

Spud and valve complete.  
Consists of H-41 & H-42.

## STRAIGHT VALVES

HALTEC NO.	TR NO.	HEIGHT	
		INCHES	MM
H-41	SP-2	11/16	15.8
H-42	TRJ-670-2	1 1/2	38.1
H-45	TRJ-670-3	1 5/8	41.3



S-8860 VALVE SUPPORT

Used for Large Bore.

S-8860

## HAND-BENDABLE EXTENSIONS

HALTEC NO.		EFFECTIVE LENGTH	
		INCHES	MM
753S-3	1/2	3 1/2	89.6
753S-4		4	101.6
753S-4	1/2	4 1/2	114.3
753S-8		8	203.2
753S-9		9	228.6
753S-10		10	254
753S-11	1/2	11 1/2	292.1
753S-12		12	304.8
753S-13	1/2	13 1/2	342.9
753S-16		16	406.4
753S-17		17	431.8
753S-17	1/2	17 1/2	444.5
753S-18		18	457.2
753S-18	1/2	18 1/2	469.9
753S-19		19	482.6
753S-20	1/2	20 1/2	520.7
753S-21		21	533.4
753S-21	1/2	21 1/2	546.1
753S-22	1/2	22 1/2	571.5
753S-23		23	584.2
753S-23	1/2	23 1/2	596.9
753S-24	1/2	24 1/2	622.3
753S-25		25	635.3
753S-29	1/2	29 1/2	749.3
753S-32		32	812.8

## EXTENSIONS

### HAND-BENDABLE

Equipped with 2 lock nuts and 3/4" hex sealing nut. A teflon gasket seals on end of valve, the lead seal in the sealing nut is forced into the threads for a second seal, positively locking extension to valve. Cap and core not included. They should be removed from valve and transferred to extension. Should be anchored to rim.

Other lengths can be ordered.



753S- LENGTH

## LARGE BORE VALVES