

EINKY VALVES

HALTEC NO.	BEND ANGLE	EFFECTIVE LENGTH	VALVE HOLE
TV-6010	STR.	3/4"	.453
TV-6020	45°	-	.453
TV-6030	STR.	1 1/4"	.453
TV-6040	STR.	1 3/4"	.453
TV-6050	90°	2 5/8"	.453



A high-performance "No Show" type chrome plated valve that installs from the outside. A rubber washer and nut are on the inside.



SNAP-IN TIRE VALVE & CHROME SLEEVE TIRE VALVES

HALTEC NO.	TR NO.	EFFECTIVE LENGTH	VALVE HOLE
TV-412	412	7/8"	.453
TV-413	413	1 1/4"	.453
TV-414	414	1 1/2"	.453
TV-415	415	1 1/4"	.625
TV-418	418	2"	.453
TV-423	423	2 1/2"	.453
TV-425	425	2"	.625
TV-413-CH	Chrome	1 1/4"	.453
TV-418-CH	Chrome	2"	.453

Maximum cold inflation pressure 65 psi.

CLAMP-IN VALVE

Used on car and light truck applications. Maximum inflation pressure 130 psi.

CLAMP-IN VALVE

HALTEC NO.	TR NO.	EFFECTIVE LENGTH	VALVE HOLE
TV-416	416	1 1/4"	.453 or .625
TV-416L	-	2"	both grommets furnished



DOUBLE BEND VALVES

For tubeless truck and bus tires. Extra-low vertical height clamp-in type. Fits .625" valve hole.

DOUBLE BEND VALVES

HALTEC NO.	TR NO.	EFFECTIVE LENGTH
TV-513	513	2 5/8"
TV-515	515	3 1/4"



H-501OV VALVE FOR 16 X 6 KS WHEEL WITH OVAL VALVE HOLE

Circumferential rim slot for valve for 16 x 6KS and 16 x 6 1/2LS rim contours.

Design allows a positive seal in this special valve hole. We recommend checking the valve hole for metal burrs prior to installation. Grommet is not replaceable.



HIGH-PRESSURE TUBELESS TIRE VALVE

HALTEC NO.	TR NO.	EFFECTIVE LENGTH	VALVE HOLE
TV-600-HP	600HP	1 1/4"	.453
TV-602-HP	602HP	2"	.453
TV-801-HP	801HP	1 1/4"	.625
TV-802-HP	802HP	2"	.625

TV-600-HP



TV-602-HP

HIGH-PRESSURE TUBELESS TIRE VALVE

TV-600-HP and TV-602-HP used to 80 psi cold inflation pressure, and fits .453" diameter valve hole, maximum rim thickness .205" at valve hole. TV-801-HP and TV-802-HP used to 100 psi cold inflation pressure, and fits .625" diameter valve hole, maximum thickness .205" at valve hole. Designed for use with transporting mobile homes.

TV-801-HP



TV-802-HP

RADIAL COMMANDER

Valve N-1147 for 15" Disc Wheels 23° bend clamp-down valve for .625 valve hole. Bend allows clearance of brake drum for tire service.



N-1147

TECH TIP

All Haltec snap-in valves pass all SAE requirements

STANDARD BORE VALVES