

## I-405 INFLATING GAUGE

Meets OSHA Requirements. Inflation unit with in-line gauge. Light-weight aluminum body with brass calibration bar and O-rings seals. Calibrated 10-120 psi in 2 lb. increments - precise inflation control - 1/4" female NPT inlet with CH-360-OP clip-on air chuck. Also available with hose lengths of 3' or 9'. Specify length when ordering.

| HALTEC NO.  | DESCRIPTION                     | HOSE LENGTH | AIR CHUCK |
|-------------|---------------------------------|-------------|-----------|
| I-405-3M    | Inflator with Clip-on Air Chuck | 3'          | CH-360-OP |
| I-405-6M    | Inflator with Clip-on Air Chuck | 6'          | CH-360-OP |
| I-405-9M    | Inflator with Clip-on Air Chuck | 9'          | CH-360-OP |
| I-405-12M   | Inflator with Clip-on Air Chuck | 12'         | CH-360-OP |
| I-405-3LOM  | Inflator with Lock-on Air Chuck | 3'          | CH-330-OP |
| I-405-6LOM  | Inflator with Lock-on Air Chuck | 6'          | CH-330-OP |
| I-405-9LOM  | Inflator with Lock-on Air Chuck | 9'          | CH-330-OP |
| I-405-12LOM | Inflator with Lock-on Air Chuck | 12'         | CH-330-OP |



I-405-3LOM

## I-405-LO INFLATING GAUGE

Same as I-405 above except with CH-330-LO lock-on chuck for use on aluminum wheels.

I-430-6



## AIR MASTER DIAL GAUGE

Haltec Air Master Dial Gauge comes in a variety of hose lengths and chuck types to meet the varied needs of the tire professional. The inflator is compact with an ergonomic design that makes the gauge comfortable to operate and easy to use. One button allows the operator to inflate or deflate. the gauge reads from 4 to 140 psi in 2 pound increments and is also calibrated from 0 to 10 bars in .1 bar increments. The dial gauge is protected with a ribbed rubber shroud.

| HALTEC NO. | DESCRIPTION         | HOSE LENGTH | AIR CHUCK |
|------------|---------------------|-------------|-----------|
| I-420      | Dial Gauge Inflator | 16"         | N-1200    |
| I-415-3    | Dial Gauge Inflator | 3'          | CH-360-OP |
| I-415-6    | Dial Gauge Inflator | 6'          | CH-360-OP |
| I-415-9    | Dial Gauge Inflator | 9'          | CH-360-OP |
| I-415-12   | Dial Gauge Inflator | 12'         | CH-360-OP |
| I-430-3    | Dial Gauge Inflator | 3'          | CH-330-OP |
| I-430-6    | Dial Gauge Inflator | 6'          | CH-330-OP |
| I-430-9    | Dial Gauge Inflator | 9'          | CH-330-OP |
| I-430-12   | Dial Gauge Inflator | 12'         | CH-330-OP |



I-406M

## I-406M INFLATING GAUGE

Has 12" of hose and CH-335 dual foot air chuck to service small diameter wheels. Gauge is calibrated 10-120 psi in 2lb increments.



## I-450 DIGITAL INFLATION GAUGE

Easy to read digital inflation unit calibrated from 0 to 150 psi in 0.5 psi increments. Available in a variety of hose lengths and chuck types to meet your needs. Entire body is protected with a rubber cover. The LCD readout is backlit for ease of reading in dark areas and the battery is replaceable.