

Haltec couplers and nipples are long-lasting, high performance products. They are rated for pressure up to 300 psi with an operating temperature range of -40° F to +250° F. The 1/4" couplers have a 4-ball locking device while the 3/8" and 1/2" series offer an 8-ball locking device. The nipples have hardened wear points and are made from solid barstock construction to provide long service life. Made in U.S.A.



### 1/4" TRU-FLATE TYPE

HALTEC NO.	DESCRIPTION	NPT	THREAD TYPE	SCHRADER	DILL	AMFLO	CAMEL	MILTON	TRU-FLATE
CO-101	Coupler	1/4"	Male	3503	D-12	C1	61-524	786	13-124
CO-103	Coupler	1/4"	Female	3504	D-13	C2	61-523	785	13-134
CO-105	Coupler	1/4"	Female	3505	-	C2R	61-487	-	-
NI-102	Nipple	1/4"	Male	3506	D-2C	CP1	61-538	783	12-124
NI-104	Nipple	1/4"	Female	3507	D-3C	CP2	61-539	784	12-134
NI-106	Nipple	fits 302-32	Female	3508	D-6C	CP12	-	779	12-104



### 1/4" ARO TYPE

HALTEC NO.	DESCRIPTION	NPT	THREAD TYPE	SCHRADER	DILL	AMFLO	CAMEL	MILTON	TRU-FLATE
CO-501	Coupler	1/4"	Female	3526	8888	C38	61-526	775	13-324
NI-502	Nipple	1/4"	Male	3529	8891	CP37	61-528	777	12-325
NI-504	Nipple	1/4"	Female	3530	8889	CP38	61-529	778	12-335



### 1/4" LINCOLN TYPE

HALTEC NO.	DESCRIPTION	NPT	THREAD TYPE	SCHRADER	DILL	AMFLO	CAMEL	MILTON	TRU-FLATE
CO-701	Coupler	1/4"	Female	3528	123	C28	61-548	790	13-434
NI-702	Nipple	1/4"	Male	3531	126	CP27	61-550	791	12-424
NI-704	Nipple	1/4"	Female	3532	125	CP28	61-551	792	12-434



### 1/4" INDUSTRIAL TYPE

HALTEC NO.	DESCRIPTION	NPT	THREAD TYPE	SCHRADER	DILL	AMFLO	CAMEL	MILTON	TRU-FLATE
NI-202	Nipple	1/4"	Male	5138-11	110	CP21	61-578	727	12-225
CO-301	Coupler*	1/4"	Female	5138-12	-	-	-	-	-
NI-204	Nipple	1/4"	Female	5139-11	109	CP20	61-579	728	12-235
CO-303	Coupler*	1/4"	Male	5139-12	-	-	-	-	-
CO-201	Coupler	1/4"	Female	5142-12	102	C20	61-573	715	13-235