

ALCOA MOUNTING HARDWARE 60° CONE SEAT CAP NUT

Each lug nut has specific inner threads for each application with universal outside threads to accept the Alcoa chrome plated nut cover (See H-78 & H-79)



16" X 7" 1 PC. LUG NUT FOR ALCOA SINGLE STUD PILOT WHEELS

HALTEC NO.	DESCRIPTION	HEX	TORQUE
5012	M12 x 1.5	7/8"	80-90 ft. lbs.
5014	M14 x 1.5	7/8"	100-110 ft. lbs.
5120	1/2 x 20	7/8"	90-100 ft. lbs.
5716	7/16 x 20	7/8"	90-100 ft. lbs.
5916	9/16 x 18	7/8"	120-140 ft. lbs.

5996R/5996L

1-1/8" x 16 Cap Nut
Mounts standard single wheels and wide base wheels to 1-1/8" studs and provides additional 1/8" hex height. Also mounts outer dual wheel to 1-1/8" inner cap nut.




5988R/5988L INNER CAP NUT

For use with standard length studs (1.31" to 1.44" stud standout) or longer studs not to exceed 1.88" stud standout. Full external threads, counter bore 5/16" deep at open end. For use with aluminum inner and outer wheels. Prevents stud from bottoming out in cap nut.

5995R/5995L

3/4" x 16 Cap Nut Mounts standard single wheels and wide base wheels to 3/4" studs.



2-PIECE FLANGE LUG NUTS OR ALCOA SINGLE & DUAL HUB-PILOT WHEELS



HALTEC NO.	DESCRIPTION	TORQUE
------------	-------------	--------

2 piece flange lug nuts (for hub pilot 16 x 6 wheels and some 19.5" RV wheels)

139698	M14 x 1.5, 1 1/16" hex	130-150 ft. lbs.
139987	9/16" x 18, 1 1/16" hex	130-150 ft. lbs.
39946	5/8" x 18, 1 1/16" hex	140-160 ft. lbs.
39913	M14x2.0, 1/16" hex	130-150 ft. lbs.

7896R/7896L INNER CAP NUT

Inner thread 3/4" x 16, outer thread 1-1/8" x 16. For use with steel inner dual wheel and aluminum outer dual wheel with 1.31" to 1.44" stud standout.



39874 - FLANGE NUT

Two-piece, 33mm hex, M22 x 1.5mm, RH thread flange nut. Mounts single and dual wheels to wheel centering hubs. Right hand threads used both sides of vehicle. Single wheels require 2" (50.8mm) stud standout. Dual wheels require 2-13/16" stud standout.



430632 - CAP NUT

Two-piece, 33mm hex, M22 x 1.5mm, RH thread, sleeved cap nut. Mounts single aluminum wheels, with 32mm bolt holes, to wheel centering hubs with stud standouts less than 1.92" (48.75mm). Right-hand threads used on both sides of vehicle.



430732 - CAP NUT

Two-piece, 33mm hex, M22 x 1.5mm, RH thread, sleeved cap nut. Mounts dual aluminum wheels, with 32mm bolt holes, to wheel centering hubs with stud standouts less than 2.85" (72mm). Right hand threads used on both sides of vehicle.