

SAFETY!

THESE PRODUCTS, AS WELL AS ALL TIRE TOOLS, SHOULD NEVER BE USED BY PERSONS UNLESS THEY HAVE BEEN TRAINED PROPERLY ACCORDING TO O.S.H.A. REGULATION #29CFR 1910.177 ENTITLED "SERVICING SINGLE-PIECE & MULTI-PIECE RIM WHEELS."



These rams are recommended for use in pushing off-rear beads on earthmover wheels. Can be used for all earthmover truck tires. Can also be used as a general purpose cylinder. Maximum operating pressure of 10,000 psi. Designed for use in all positions. Made in USA. A coupler and dust cap are included with all models.

HYDRAULIC RAMS & JACKS

HALTEC NO.	CYLINDER CAPACITY (TONS)	STROKE (INCHES)	CYLINDER EFFECTIVE AREA (IN ²)	OIL CAPACITY (IN ³)	COLLAPSED HEIGHT (IN)	WEIGHT (LBS.)
AJ-102	10	2.13	2.23	4.75	4.78	5.1
AJ-106	10	6.13	2.23	13.67	9.75	9.4
AJ-110	10	10.13	2.23	22.59	13.75	12.9
AJ-30	30	2.44	6.5	15.85	4.5	13.8
AJ-506	50	6	11.05	66.3	10.97	31.5
AJ-1006	100	6	20.65	136.91	14.06	45

AJ-30

The AJ-30 "shorty" is a light-weight, low-profile design for use in confined places. Cylinder capacity is 30 tons.

AJ-506-B

The AJ-506B 50-ton aluminum jack is easy-to-handle and light-weight, it can be used with any 10,000 psi pump. Perfect for off-highway work. Comes with a 7" x 7" aluminum base.

AJ-506AB

7" x 7" aluminum base for use with the AJ-506.



HYDRAULIC RAMS & JACKS