



30606 – PROFESSIONAL LUG NUT COVER REMOVER

Special coating will not scratch or damage chrome, painted, or coated lug nut covers.



T147A - 35847 BEAD-EZE® TIRE LUBRICANT

Lubricates tire and rim for ease in mounting. Dries quickly. Makes excellent leak detector when diluted. Size: 1 gallon; Weight: 9 lbs. (4.1kg)



39730 - MACPHERSON STRUT COIL SPRING COMPRESSOR SET

Compressor works on most MacPherson Strut assemblies and is for use with replacements. Use the compressor when replacing bent strut or strut tube and damaged spindles. Use it on or off the car. Acme threaded screw for durability. Do not use on General Motors "A", "C", "J" or "X" body cars. Weight: 7 lbs. (3.1kg).



T950 – IRONMAN™ ERGONOMIC WHEEL LIFTING BAR

Use the leverage created by the tool, not your back! Reduces back strain. Easily and safely lift heavy, awkward truck tire and wheel assemblies. Specially designed forged ends work from either side of the wheel assembly as it lays flat. Extremely useful in outdoor conditions – when truck tire and wheel assemblies can become wet and slippery. Lift all sizes and types of small and large heavy truck wheels: Standard sizes including 22.5" and 24.5" wheels, plus European (which have 1" lug holes), Super Wide and even the Super Single (a 340 lb. assembly) size. Length: 58" (147cm); Weight: 10 lbs (435kg).



30115 –THREE PIECE LUG AND LOCK FLIP SOCKET SET

One end is a standard 6-fluted twist socket for removing damaged wheel lugs. Flip socket over and you have a 12-fluted twist socket for removing wheel locks. Drive: 1/2"; Socket Sizes: 19mm, 3/4" socket; 7/8" socket; 3" extension; Weight: 1.6 lbs. (.7kg).

PNEUMATIC BEAD EXPANDERS

Expanders fit most bias ply passenger tires. A pliable neoprene rubber tube is encased in a tough, long-lasting nylon cover. Expanders slip easily over tire and withstand contact with oil, grease, solvents, and acids. Follow instructions included with tool. Use on belted bias ply tires, 14", 15", 70-series tires and larger. Expands bead by compressing tread. T132 for belted bias ply tires, includes over-pressure release valve. T133 for standard bias ply tires.

PNEUMATIC BEAD EXPANDERS

| PART NO. | EDP NO. | MIN/MAX DIAMETER | TUBE DIAMETER | WEIGHT |
|----------|---------|-------------------|---------------|------------------|
| T132 | 31432 | 24-34" (61-86 cm) | 2-1/4" (6 cm) | 2.8 lbs (1.2 kg) |
| T133 | 31433 | 22-32" (60-81 cm) | 3/4" (2 cm) | .75 lbs (.3 kg) |

HAMMERS:



T34RH - 35105 REPLACEMENT RUBBER HEAD

Replacement rubber head for use on Ken-Tool Heavy-Duty Tire Hammers.



T32 - 35310 2 LB. RUBBER Mallet

Rubber head minimizes marring surfaces. Length: 17".



T68 - 31568 STANDARD WHEEL COVER PULLER/REPLACER

Removes wheel covers quickly and easily without gouging or scratching them. Rubber head T11RH prevents damage to hubcap and is replaceable. Length: 14" (36cm); Stock: 7/16" (11.1cm); Weight: 1.3 lbs. (.6kg).

