

OTR-TDT

- » Deflator greatly decreases the time and money it takes to deflate a large OTR tire
- » Operates most effectively when using a compressor producing 155 cfm @ 150 PSI
- » Comes equipped with heavy duty axels and flat free pneumatic tires
- » Low maintenance tool with short term ROI
- » Easy to service air exhaust muffler
- » The tool has been engineered and certified
- » Quiet - operates at 80 dB
- » Comes equipped with:
 - Cold weather 25' air line rated for 300 PSI replacing the industries standard 15'-20' safety deflation/ inflation air lines being used
 - Valve stem adapter - c/w unions for both the SLB, Z-Bore, and Mega-Bore size valve stems
 - Weather-guard muffler rain cover



OTR-TDC-SYS

- » Enclosure protects the deflation equipment from falling debris
- » Side and rear vents allow the deflator to release air from within the enclosure
- » Sliding control panel door used to protect the gauges and control valves
- » Rear vent is removable so that the deflation filters can be cleaned
- » Handle is designed to be pulled with a pintle hook or pulled by hand
- » Top is designed to be used as a tool or equipment tray
- » Optional beacon light to notify the user when the tire is deflated to a safe level

OTR-WALL MOUNT

- » 42" L X 18" W mounting plate (custom sizes available)
- » Equipped with 2 1/2" PVC coupler on the exhaust side
- » Comes with a 20' reinforced inflation/deflation air line

